

## GU79XX

### 3-TERMINAL NEGATIVE VOLTAGE REGULATORS



#### Description

The GU79XX series of fixed-voltage monolithic integrated-circuit voltage regulators are designed to complement Series GU78XX in a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. Each of these regulators can deliver up to 1.0 amperes of output current. The internal current limiting and thermal shutdown features of these regulators make them essentially immune to overload. In addition to use as fixed-voltage regulators, these devices can be used with external components to obtain adjustable output voltage and current and also as the power pass element in precision regulators.

#### Features

- -5V, -6V, -8V, -9V, -12V, -15V, -18V, -24V output voltage available
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limiting
- No External Components
- Output Transistor Safe-Area Compensation

#### Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	4.40	4.80	c2	1.25	1.45
b	0.76	1.00	b2	1.17	1.47
L4	0.00	0.30	D	8.6	9.0
c	0.36	0.5	e	2.54 REF.	
L3	1.50 REF.		L	14.6	15.8
L1	2.29	2.79	θ	0°	8°
E	9.80	10.4	L2	1.27 REF.	

#### Absolute Maximum Ratings (Ta=25°C)

Parameter		Ratings	Unit
Input voltage	GU7905 ~ 18	-35V	V
	GU7924	-40V	V
Output current		1.0	A
Operating junction temperature range		0 ~ 150	°C
Storage temperature range		-55 ~ 150	°C
Thermal resistance junction-air (RθJA)		65	°C/W
Thermal resistance junction-cases (RθJC)		5	°C/W

## Electrical Characteristics

**GU7905** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-10\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-4.85	-5.0	-5.15	V	$V_{in}=-10\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-4.75	-	-5.25		$-7\text{V} \leq V_{in} \leq -20\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $\text{PD} \leq 15\text{W}$
$\Delta\text{VO}$ (Line Regulation)		-	10	50	mV	$-7\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	-	25		$-8\text{V} \leq V_{in} \leq -12\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta\text{VO}$ (Load Regulation)		-	10	100	mV	$V_{in}=-10\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	3	50		$V_{in}=-10\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-10\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta\text{IQ}$		-	-	0.5	mA	$V_{in}=-10\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.3		$-7\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$
Vn		-	100	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-8\text{V} \leq V_{in} \leq -18\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta\text{Vo} / \Delta T_j$		-	-0.4	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7906** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-11\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-5.82	-6.0	-6.18	V	$V_{in}=-11\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-5.70	-	-6.30		$-8\text{V} \leq V_{in} \leq -21\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $\text{PD} \leq 15\text{W}$
$\Delta\text{VO}$ (Line Regulation)		-	10	120	mV	$-8\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	5	60		$-9\text{V} \leq V_{in} \leq -13\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta\text{VO}$ (Load Regulation)		-	10	120	mV	$V_{in}=-11\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	3	60		$V_{in}=-11\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-11\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta\text{IQ}$		-	-	0.5	mA	$V_{in}=-11\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.3		$-8\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$
Vn		-	130	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-9\text{V} \leq V_{in} \leq -19\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta\text{Vo} / \Delta T_j$		-	-0.5	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7908** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-14\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-7.76	-8.0	-8.24	V	$V_{in}=-14\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-7.60	-	-8.40		$-10.5\text{V} \leq V_{in} \leq -23\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $PD \leq 15\text{W}$
$\Delta VO$ (Line Regulation)		-	10	160	mV	$-10.5\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	5	80		$-11.5\text{V} \leq V_{in} \leq -17\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta VO$ (Load Regulation)		-	12	160	mV	$V_{in}=-14\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	4	80		$V_{in}=-14\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-14\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta IQ$		-	-	0.5	mA	$V_{in}=-14\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.0		$-11.5\text{V} \leq V_{in} \leq -25\text{V}$ , $I_o=500\text{mA}$
Vn		-	175	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-11.5\text{V} \leq V_{in} \leq -21.5\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta Vo / \Delta Tj$		-	-0.6	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7909** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-15\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-8.73	-9.0	-9.27	V	$V_{in}=-15\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-8.55	-	-9.45		$-11.5\text{V} \leq V_{in} \leq -23\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $PD \leq 15\text{W}$
$\Delta VO$ (Line Regulation)		-	10	180	mV	$-11.5\text{V} \leq V_{in} \leq -26\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	5	90		$-12\text{V} \leq V_{in} \leq -18\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta VO$ (Load Regulation)		-	12	180	mV	$V_{in}=-15\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	4	90		$V_{in}=-15\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-15\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta IQ$		-	-	0.5	mA	$V_{in}=-15\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.0		$-11.5\text{V} \leq V_{in} \leq -26\text{V}$ , $I_o=500\text{mA}$
Vn		-	175	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-12.5\text{V} \leq V_{in} \leq -22.5\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta Vo / \Delta Tj$		-	-0.6	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7912** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-19\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-11.64	-12.0	-12.36	V	$V_{in}=-19\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-11.40	-	-12.60		$-14.5\text{V} \leq V_{in} \leq -27\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $PD \leq 15\text{W}$
$\Delta VO$ (Line Regulation)		-	12	240	mV	$-14.5\text{V} \leq V_{in} \leq -30\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	6	120		$-16\text{V} \leq V_{in} \leq -22\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta VO$ (Load Regulation)		-	12	240	mV	$V_{in}=-19\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	4	120		$V_{in}=-19\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-19\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta IQ$		-	-	0.5	mA	$V_{in}=-19\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.0		$-14.5\text{V} \leq V_{in} \leq -30\text{V}$ , $I_o=500\text{mA}$
Vn		-	200	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-15\text{V} \leq V_{in} \leq -25\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta Vo / \Delta Tj$		-	-0.8	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7915** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-23\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)


Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-14.55	-15.0	-15.45	V	$V_{in}=-23\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
	B-Rank (5%)	-14.25	-	-15.75		$-17.5\text{V} \leq V_{in} \leq -30\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $PD \leq 15\text{W}$
$\Delta VO$ (Line Regulation)		-	12	300	mV	$-17.5\text{V} \leq V_{in} \leq -30\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
		-	6	150		$-20\text{V} \leq V_{in} \leq -26\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta VO$ (Load Regulation)		-	12	300	mV	$V_{in}=-23\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$ , $T_j=25^{\circ}\text{C}$
		-	4	150		$V_{in}=-23\text{V}$ , $250\text{mA} \leq I_o \leq 750\text{mA}$ , $T_j=25^{\circ}\text{C}$
IQ		-	-	6.0	mA	$V_{in}=-23\text{V}$ , $I_o=500\text{mA}$ , $T_j=25^{\circ}\text{C}$
$\Delta IQ$		-	-	0.5	mA	$V_{in}=-23\text{V}$ , $5\text{mA} \leq I_o \leq 1\text{A}$
		-	-	1.0		$-17.5\text{V} \leq V_{in} \leq -30.5\text{V}$ , $I_o=500\text{mA}$
Vn		-	250	-	$\mu\text{V}$	$10\text{Hz} \leq f \leq 100\text{KHz}$ , $T_a=25^{\circ}\text{C}$
RR		54	-	-	dB	$-18.5\text{V} \leq V_{in} \leq -28.5\text{V}$ , $f=120\text{Hz}$ , $T_j=25^{\circ}\text{C}$
VD		-	2	-	V	$I_o=1\text{A}$ , $T_j=25^{\circ}\text{C}$
Ipk		-	2.2	-	A	$T_j=25^{\circ}\text{C}$
$\Delta Vo / \Delta Tj$		-	-0.9	-	$\text{mV}/^{\circ}\text{C}$	$I_o=5\text{mA}$ , $0^{\circ}\text{C} \leq T_j \leq 125^{\circ}\text{C}$

**GU7918** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-27\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-17.46	-18.0	-18.54	V	Vin=-27V, Io=500mA, , Tj=25℃ -21V ≤ Vin ≤ -33V, 5mA ≤ Io ≤ 1A, PD ≤ 15W
	B-Rank (5%)	-17.10	-	-18.9		
ΔVO (Line Regulation)		-	15	360	mV	-21V ≤ Vin ≤ -33V, Io=500mA, Tj=25℃
		-	8	180		-24V ≤ Vin ≤ -30V, Io=500mA, Tj=25℃
ΔVO (Load Regulation)		-	15	360	mV	Vin=-27V, 5mA ≤ Io ≤ 1A, Tj=25℃
		-	5	180		Vin=-27V, 250mA ≤ Io ≤ 750mA, Tj=25℃
IQ		-	-	6.0	mA	Vin=-27V, Io=500mA, Tj=25℃
Δ IQ		-	-	0.5	mA	Vin=-27V, 5mA ≤ Io ≤ 1A
		-	-	1.0		-21V ≤ Vin ≤ -33V, Io=500mA
Vn		-	300	-	μV	10Hz ≤ f ≤ 100KHz, Ta=25℃
RR		54	-	-	dB	-22V ≤ Vin ≤ -32V, f=120Hz, Tj=25℃
VD		-	2	-	V	Io=1A, Tj=25℃
Ipk		-	2.2	-	A	Tj=25℃
ΔVo / ΔTj		-	-1.0	-	mV/℃	Io=5mA, 0℃ ≤ Tj ≤ 125℃

**GU7924** (Refer to the test circuits,  $T_j=0\sim 125^{\circ}\text{C}$ ,  $I_o=500\text{mA}$ ,  $V_{in}=-33\text{V}$ ,  $C_{in}=2.2\mu\text{F}$ ,  $C_o=1\mu\text{F}$  unless otherwise specified)

Symbol		Min.	Typ.	Max.	Unit	Test Conditions
VO	A-Rank (3%)	-23.28	-24.0	-24.72	V	Vin=-33V, Io=500mA, Tj=25°C -27V ≤ Vin ≤ -38V, 5mA ≤ Io ≤ 1A, PD ≤ 15W
	B-Rank (5%)	-22.80	-	-25.20		
ΔVO (Line Regulation)		-	15	480	mV	-27V ≤ Vin ≤ -38V, Io=500mA, Tj=25°C
		-	8	240		-30V ≤ Vin ≤ -36V, Io=500mA, Tj=25°C
ΔVO (Load Regulation)		-	15	480	mV	Vin=-33V, 5mA ≤ Io ≤ 1A, Tj=25°C
		-	5	240		Vin=-33V, 250mA ≤ Io ≤ 750mA, Tj=25°C
IQ		-	-	6.0	mA	Vin=-33V, Io=500mA, Tj=25°C
Δ IQ		-	-	0.5	mA	Vin=-33V, 5mA ≤ Io ≤ 1A
		-	-	1.0		-27V ≤ Vin ≤ -38V, Io=500mA
Vn		-	400	-	μV	10Hz ≤ f ≤ 100KHz, Ta=25°C
RR		54	-	-	dB	-28V ≤ Vin ≤ -38V, f=120Hz, Tj=25°C
VD		-	2	-	V	Io=1A, Tj=25°C
Ipk		-	2.2	-	A	Tj=25°C
ΔVo / ΔTj		-	-1.0	-	mV/°C	Io=5mA, 0°C ≤ Tj ≤ 125°C

**Typical Application****Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165