

NZ9F2V4ST5G SERIES

Zener Voltage Regulators

200 mW SOD-923 Surface Mount

This series of Zener diodes is packaged in a SOD-923 surface mount package. They are designed to provide voltage regulation protection and are especially attractive in situations where space is at a premium. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.

Specification Features

- Standard Zener Breakdown Voltage Range -2.4 V to 18 V
- Steady State Power Rating of 200 mW
- Small Body Outline Dimensions:
0.039" x 0.024" (1.00 mm x 0.60 mm)
- Low Body Height: 0.016" (0.40 mm)
- ESD Rating of Class 3 (>16 kV) per Human Body Model
- Tight Tolerance V_Z
- These are Pb-Free Devices

Mechanical Characteristics

CASE: Void-free, transfer-molded, thermosetting plastic
Epoxy Meets UL 94, V-0

LEAD FINISH: 100% Matte Sn (Tin)

MOUNTING POSITION: Any

QUALIFIED MAX REFLOW TEMPERATURE: 260°C

Device Meets MSL 1 Requirements

MAXIMUM RATINGS

Rating	Symbol	Max	Unit
Total Device Dissipation FR-5 Board, (Note 1) @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	200 1.5	mW mW/°C
Thermal Resistance from Junction-to-Ambient	$R_{\theta JA}$	635	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	-65 to +150	°C



Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. FR-4 Minimum Pad.




ON Semiconductor®

<http://onsemi.com>



**SOD-923
CASE 514AB**

MARKING DIAGRAM



X = Specific Device Code
M = Month Code
• = Pb-Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NZ9FxxxST5G	SOD-923 (Pb-Free)	8000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

DEVICE MARKING INFORMATION

See specific marking information in the device marking column of the Electrical Characteristics table on page 3 of this data sheet.

NZ9F2V4ST5G SERIES

ELECTRICAL CHARACTERISTICS

($T_A = 25^\circ\text{C}$ unless otherwise noted,
 $V_F = 0.9\text{ V Max. @ } I_F = 10\text{ mA}$ for all types)

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZK}	Reverse Current
Z_{ZK}	Maximum Zener Impedance @ I_{ZK}
I_R	Reverse Leakage Current @ V_R
V_R	Reverse Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F
ΘV_Z	Maximum Temperature Coefficient of V_Z
C	Max. Capacitance @ $V_R = 0$ and $f = 1\text{ MHz}$




Figure 1. Zener Voltage Regulator




Figure 2. Steady State Power Derating

NZ9F2V4ST5G SERIES

ELECTRICAL CHARACTERISTICS ($V_F = 0.9$ Max @ $I_F = 10$ mA for all types)

Device	Device Marking	Zener Voltage VZ		Test Current Izt mA	Z _{KT} I _Z = I _{ZT} @ 10% Mod Ω Max	Z _{ZK} I _Z = 1.0 mA Ω Max	I _{ZK} mA	Max IR @ VR		dV _Z /dt (mV/k) @ I _{ZT1} = 5 mA		CpF Max @ V _R = 0 f = 1 MHz
		Min	Max					μA	V	Min	Max	
NZ9F2V4ST5G	2*	2.43	2.63	5	100	1000	1	50	1	-3.5	0	210
NZ9F2V7ST5G	3*	2.67	2.91	5	100	1000	1	20	1	-3.5	0	210
NZ9F3V0ST5G	4*	2.94	3.26	5	100	1000	1	10	1	-3.5	0	210
NZ9F3V3ST5G	5*	3.32	3.53	5	100	1000	1	10	1	-3.5	0	210
NZ9F3V6ST5G	6*	3.6	3.85	5	100	1000	1	10	1	-3.5	0	210
NZ9F3V9ST5G	A**	3.89	4.16	5	100	1000	1	5	1	-3.5	-2.5	210
NZ9F4V3ST5G	D**	4.17	4.43	5	100	1000	1	5	1	-3.5	0	210
NZ9F4V7ST5G	E**	4.55	4.75	5	100	800	0.5	2	1	-3.5	0.2	150
NZ9F5V1ST5G	F**	4.989	5.2	5	80	500	0.5	2	1.5	-2.7	1.2	130
NZ9F5V6ST5G	J**	5.49	5.73	5	60	200	0.5	1	2.5	-2.0	2.5	115
NZ9F6V2ST5G	K**	6.06	6.33	5	60	100	0.5	1	3	0.4	3.7	110
NZ9F6V8ST5G	L**	6.65	6.93	5	40	60	0.5	0.5	3.5	1.2	4.5	105
NZ9F7V5ST5G	P**	7.28	7.6	5	30	60	0.5	0.5	4	2.5	5.3	100
NZ9F8V2ST5G	Q**	8.02	8.36	5	30	60	0.5	0.5	5	3.2	6.2	90
NZ9F9V1ST5G	R**	8.85	9.23	5	30	60	0.5	0.5	6	3.8	7	80
NZ9F10VST5G	T**	9.77	10.21	5	30	60	0.5	0.1	7	4.5	8	80
NZ9F11VST5G	V**	10.76	11.22	5	30	60	0.5	0.1	8	5.4	9	80
NZ9F12VST5G	Y**	11.74	12.24	5	30	80	0.5	0.1	9	6	10	80
NZ9F13VST5G	2**	12.91	13.49	5	37	80	0.5	0.1	10	7	11	75
NZ9F15VST5G	3**	14.34	14.98	5	42	80	0.5	0.1	11	9.2	13	70
NZ9F16VST5G	4**	15.85	16.51	5	50	80	0.5	0.1	12	10.4	14	65
NZ9F18VST5G	5**	17.56	18.35	5	50	80	0.5	0.1	14	12.4	16	60


*Rotated 90°.

**Rotated 180°.

NZ9F2V4ST5G SERIES

PACKAGE DIMENSIONS

SOD-923
CASE 514AB-01
ISSUE B




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.


DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.34	0.37	0.40	0.013	0.015	0.016
b	0.15	0.20	0.25	0.006	0.008	0.010
c	0.07	0.12	0.17	0.003	0.005	0.007
D	0.75	0.80	0.85	0.030	0.031	0.033
E	0.55	0.60	0.65	0.022	0.024	0.026
H_E	0.95	1.00	1.05	0.037	0.039	0.041
L	0.05	0.10	0.15	0.002	0.004	0.006

SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

NZ9F2V4S/D