

4

3

2

1

used for:

D-SUB

SW 5
e=5.77

4-40 UNC

5

13

4-40 UNC

SCREW

WASHER $\phi 6/3 \times 0.8$

SPRING RING DIN127 A3

NUT 4-40 UNC
SW 5x2.2


1 SET CONSISTS OF:
 2 SCREWS
 2 WASHERS
 2 SPRING RINGS
 2 NUTS

Directive 2002/95/EC
 „RoHS“
 Compliant

THIS DRAWING MAY NOT BE COPIED OR
 REPRODUCED IN ANY WAY, AND MAY NOT
 BE PASSED ON TO A THIRD PARTY WITHOUT
 WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

CONEC CORPORATION
 BRAMPTON, ONTARIO

tolerance



scale:

5:1

material:

COPPER ALLOY
 NICKEL PLATED

title:

SCREW LOCKING
 Type 1 / 4-40 UNC / 13mm

dwg no:

AutoCAD 2000

DIN-A

16K1A166A

4

sh: 1/1

part no:

160X10359X

rev.	description	date	name

CONEC[®]

4

3

2

www.DataSheet4U.com